Safety Data Sheet

Galv-A-Guard

SECTION I - IDENTIFICATION

PRODUCT NAME: Galv-A-Guard COMPANY NAME: ATCO International COMPANY PHONE: 1-800-723-2826

PRODUCT CODE: 3780

PRODUCT USE: Stop rust and corrosion

COMPANY ADDRESS: 1401 Barclay Circle, S.E. Marietta, GA 30060

EMERGENCY PHONE: 800-255-3924

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1 Liquefied Gas

Skin Irritant: Category 2 Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category

3 Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.







SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

Product is listed ingredients with non-hazardous additives.

 HAZARDOUS INGREDIENT
 CAS NUMBER
 PERCENT

 Heptane
 142-82-5
 10-30%

 Acetone
 67-64-1
 7-13%

 Propane/n-Butane
 68476-86-8
 15-40%

 Xylene
 1330-20-7
 1-5%

Exact names and percentages of listed ingredients are with held as trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice or attention. INGESTION: Immediately call a poison center or doctor. Do NOT induce vomiting. INHALATION:

Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. SKIN: Wash thoroughly with soap and water. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis Inhalation: Anesthetic, irritation,

Centralervous System depression Oral: abdominal irritation, nausea,

vomiting, diarrhea, and aspiration risk

CHRONIC HEALTH HAZARDS: Skin disorders, drying and irritation of the skin.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam and water fog. **UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream. **SPECIAL FIRE FIGHTING PROCEDURES:** Wear full protective clothing and NIOSH approved SCBA with full face piece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

PAGE 1 of 4

Safety Data Sheet Galv-A-Guard

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Containers may be hazardous when empty.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII - HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	500 ppm	400 ppm
Acetone	1000 ppm	500 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Xylene	100 ppm	100 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded. **PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling. Do not breathe vapors. Do not eat, drink, or smoke while using product. Get medical attention if you feel unwell.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Gray Aerosol Spray

ODOR: Solvent odor

ODOR THRESHOLD: N/D

BOILING POINT: N/D

FREEZING POINT: N/D FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: N/D

LOWER FLAMMABILITY LIMIT: N/A

VAPOR PRESSURE (mm Hg): N/D

EVAPORATION RATE: >3 Fast

AUTOIGNITION TEMPERATURE: N/D

UPPER FLAMMABILITY LIMIT: N/A

VAPOR DENSITY (AIR=1): >2

SPECIFIC GRAVITY (H2O=1): 1.23

pH: N/A SOLIDS (%): 40.5%

SOLUBILITY IN WATER: Moderate PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

VOLATILITY INCLUDING WATER (%): 66% VOLATILE ORGANIC COMPOUNDS (VOC): 58%

DIELECTRIC STRENGTH (Volts): N/D DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: 14cps

SECTION X - STABILITY AND REACTIVITY DATA

REACTIVITY: If exposed to strong oxidizers, presents explosion hazard.

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.

INCOMPATIBILITY: Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon

POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone (67-64-1) LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8hr) 50100 mg/m³; LC50 (Inhalation, Mouse, 4hr) 44,000 mg/m³ Heptane (142-82-5) LC50 (Inhalation, Rat): 103,000 mg/m³

Safety Data Sheet

Galv-A-Guard

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin **EYES:** Causes moderate irritation, redness, tearing.

INGESTION: May cause effects similar to those for inhalation exposure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. May cause central nervous system depression. Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomitting, abdominal cramps.

INHALATION: Dizziness, headache, nausea, depression of central nervous system, prolonged exposure may lead to unconsciousness

SKIN: Brief contact is not irritating. May cause irritation, localized defatting, redness, itching with prolonged or repeated contact. Can be absorbed through the skin with prolonged and widespread contact.

MEDICAL CONDITION AGGRAVATED: None known

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

CHRONIC HEALTH HAZARDS: Skin disorders, drying and irritation of the skin.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

SECTION XII - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Acetone (67-64-1) LCso (Trout, 96hr) 5540 mg/L; LCso (Bluegill, 96hr) 8300 mg/L; LCso (Fathead Minnow, 96hr) 7500 mg/L

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: This product is not expected to bioaccumulate.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: This material is toxic to aquatic life.

SECTION XIII - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Containers may be hazardous when empty.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

UN/NA NUMBER:

UN 1950

HAZARD CLASS/DIVISION: 2.1

PACKAGING GROUP:

N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty. HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty. HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950 ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 lbs

Xylenes (1330-20-7) Reportable Quantity = 100 lbs **SARA 311/312 HAZARD CATEGORIES:** Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: Xylenes - 1330-20-7

STATE REGULATIONS: Heptane (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH:2HMIS HEALTH:2NFPA FLAMMABILITY:3HMIS FLAMMABILITY:3NFPA REACTIVITY:1HMIS REACTIVITY:1NFPA OTHER:NoneHMIS PROTECTION:B

Safety Data Sheet Galv-A-Guard

SECTION XVI - ADDTIONAL INFORMATION

PREPARATION BY: Technical Services DATE PREPARED: 07/24/2013 REVISION DATE: 11/24/2014

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.