

Product Data

GALV-A-GUARD

**Galvanized Zinc
Protective Coating**

- ✓ Prevents Rust Creepage
- ✓ Stops Corrosion
- ✓ Electro-Chemical Zinc Bond
- ✓ Economical
- ✓ Long Lasting

APPLICATIONS

GALV-A-GUARD provides a zinc film on metal surfaces that seals out moisture and prevents corrosion by sacrificial galvanic action. It is highly resistant to water, acid and salt atmospheres.

Typically used on structural steel and wire, truck and auto bodies, gutter and down spouts, boats, trailers, docks, farm and road equipment, signs, fencing, tanks, piping, fans, ducts, culverts, air conditioning units, ornamental and antique metals, dairy equipment and oil rigs.

DIRECTIONS

Shake can for a full sixty (60) seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Remove protective cap and point opening in spray nozzle towards surface to be sprayed. Holding can 10 to 12 inches from the surface, apply in thin, even coats until surface is completely covered. Allow 5 to 10 minutes after application before handling. After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80°F).

TECHNICAL DATA

FORM: Solvent Based Aerosol

FLASH POINT: 65°F TCC

ODOR: Solvent

FLAME EXTENSION: 18"

COLOR: Gray

SOLUBILITY IN WATER: 0%

DETERGENCY: None

SPECIFIC GRAVITY: 1.20

TOXICITY: 100 ppm OSHA TLV

% VOLATILE BY VOLUME: 66%

WETTING ABILITY: N/A

pH: N/A

STORAGE STABILITY: 1 Year

PROPELLANT: Hydrocarbon

COLD STABILITY: 32°F

EVAPORATION RATE: Medium

PHOSPHATES: None

BIODEGRADABILITY: No

TEMPERATURE TOLERANCE: Continuous 250°F
Intermittent 300°F