

PRODUCT DATA

BAR & CHAIN OIL

DESCRIPTION

Bar and Chain Oil is a unique blend of the finest refined petroleum stocks and additives available, designed to provide the chain saw owner with the maximum protection against bar and chain wear.

APPLICATIONS

Bar and Chain Oil may safely be used in all makes of chain saws on the market today as a bar and chain lubricant.

ADVANTAGES

COMPARE THESE FEATURES AGAINST ANY OF THE LEADING BAR AND CHAIN OILS ON THE MARKET TODAY:

- ⇒ GREATLY REDUCES BAR BURNING AND CHAIN WEAR. HAS EXCELLENT PENETRATING AND EXTREME PRESSURE PROPERTIES - more than pays for itself in savings through reduced fuel consumption and replacement parts!
- ⇒ FEEDS EVENLY AND PRECISELY - one grade for year-round use, no need to change oil with temperature changes!
- ⇒ POSSESSES EXCELLENT RESISTANCE TO "THROW-OFF" - conditions and protects chain pins and bushings against rust while not contributing to dust-to-dust load-up!
- ⇒ IS NON-GUMMING - assures top operating performance of your chain saws, month in and month out!
- ⇒ ADHERES BETTER - requires less frequent lubrication intervals in manually operated bar and chain lubricators!
- ⇒ CUTTING CHAIN OPERATES COOLER - protects cutting teeth, teeth remain sharper longer!

PROTECT THE INVESTMENT YOU HAVE MADE IN YOUR CHAIN SAW . . . USE ONLY BAR AND CHAIN OIL!



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Viscosity: SUS @ 100°F	ASTM D-2161	347
cSt @ 40°C	ASTM D-445	67
SUS @ 210°F	ASTM D-2161	53
cSt @ 100°C	ASTM D-445	8
Flash Point	ASTM D-92	395°F/202°C
Fire Point	ASTM D-92	430°F/221°C
Pour Point	ASTM D-97	-30°F/-34°C
SAE Grade		20
Color	ASTM D-1500	L-3

PACKAGING AVAILABLE

Carton, 12/1 Quart Plastic Bottles
Carton, 4/1 Gallon Jugs
55 Gallon Drum

Part No.

L0720-054
L0720-057
L0720-062